

## DS-9600NI-I24 SERIES NVR



### Features and Functions

#### Professional and Reliable

- New logical and visualized GUI design.
- Adopts professional embedded hardware and software, and pioneering dual-OS design to ensure the reliability of system running.
- Supports redundant power supply to improve the system stability.
- Supports HDD hot swap with RAID0, RAID1, RAID5, RAID 6, and RAID10 storage scheme configurable.
- Either normal or hot spare working mode is configurable to constitute an N+1 hot spare system.

#### Video Input and Transmission

- Up to 128/256 IP cameras can be connected.
- Supports live view, storage, and playback of the connected camera at up to 12 megapixels resolution.
- H.265+ compression effectively reduces the storage space by up to 75%.
- 4 self-adaptive 10M/100M/1000M network interfaces.
- Adopt stream over TLS encryption technology (enhanced SDK service and RTP over HTTPS protocol)
- Connectable to the third-party network cameras like ACTI, Arecont, AXIS, Bosch, Brickcom, Canon, ONVIF, PANASONIC, Pelco, SAMSUNG, SANYO, SONY, Vivotek and ZAVIO.

#### HD Output

- Simultaneous HDMI 1/VGA output as the main output and the HDMI 2 works as the auxiliary output.
- HDMI and VGA1 simultaneous outputs by default. Asynchronous outputs configurable.
- Video outputs at up to 4K (4096×2160) resolution.
- Supports decoding up to 20 channels at 1080p resolution.

#### HD Storage

- Up to 24 SATA interfaces and 1 eSATA interface provided for HDD connection.
- 10 TB capacity for each HDD.
- HDD health monitoring.
- Supports HDD quota and group modes; different capacity can be assigned to different channels.
- Normal/Important/Custom video playback.

#### Various Applications


- Centralized management of IP cameras is supported, including configuration, information import/export, real-time information display, two-way audio, upgrade, etc.
- Connectable to smart IP cameras from Hikvision and the recording, playing back, and backing up of VCA alarms can be realized.
- VCA detection alarm is supported.
- VCA search for facial detection, behavior analysis, people counting and heat map.
- Supports starting record with one key.
- Realizes instant playback for assigned channel during multi-channel display mode.
- Smart search for the selected area in the video; and smart playback to improve the playback efficiency.



## Specifications

| Model                  |   | DS-96128NI-I24   | DS-96256NI-I24    |
|------------------------|---|--|-------------------|
| Video & Audio input    | IP video input                          | 128-ch   | 256-ch            |
|                        | Incoming/outgoing bandwidth             | 576 Mbps/512 Mbps  | 768 Mbps/768 Mbps |
|                        | Incoming/outgoing bandwidth (RAID mode) | 576 Mbps/512 Mbps  | 768 Mbps/768 Mbps |
|                        | TLS outgoing bandwidth                  | 128 Mbps, or 64 Mbps (when RAID is enabled)  |                   |
|                        | Protocol                                | HIKVISION, ACTi, ARECONT, AXIS, BOSCH, BRICKCOM, CANON, HUNT, ONVIF (Version 2.5), PANASONIC, PELCO, RTSP, SAMSUNG, SONY, VIVOTEK, ZAVIO   |                   |
| Video & Audio output   | HDMI output                             | Two independent HDMI outputs of 4K resolution. Resolution: 4K (4096 × 2160), 4K (3840 × 2160)/30Hz, 2K (2560 × 1440)/60Hz, 1080p (1920 × 1080)/60Hz, UXGA (1600 × 1200)/60Hz, SXGA (1280 × 1024)/60Hz, 720p (1280 × 720)/60Hz, XGA (1024 × 768)/60Hz |                   |
|                        | VGA output                              | 1-ch. Resolution: 1080p (1920 × 1080)/60Hz, UXGA (1600 × 1200)/60Hz, SXGA (1280 × 1024)/60Hz, 720p (1280 × 720)/60Hz, XGA (1024 × 768)/60Hz  |                   |
|                        | LCD output (optional)                   | One 7 inch LCD   |                   |
|                        | Audio output                            | 1-ch. RCA (2.0 Vp-p, 1 KΩ)   |                   |
| Video & Audio decoding | Decoding format                         | H.265, H.265+, H.264, H.264+, MPEG4, MJPEG (for Hikvision IP camera only)  |                   |
|                        | Video resolution                        | 12 MP/8 MP/7 MP/6 MP/5 MP/4 MP/3 MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF  |                   |
|                        | Synchronous playback                    | Up to 16 channels  |                   |
|                        | Capability                              | 3-ch@12 MP (30fps), 5-ch@8 MP (30fps), 6-ch@6 MP (30fps), 10-ch@4 MP (30fps), 20-ch@1080p (30 fps)   |                   |
| HDD                    | Interface                               | 24 SATA interfaces supporting hot-plug   |                   |
|                        | Capacity                                | Up to 10 TB for each HDD   |                   |
|                        | Storage extension                       | 1 × eSATA interface, 2 × mini SAS interface (optional)   |                   |
| RAID                   | RAID Type                               | RAID0, RAID1, RAID5, RAID 6, and RAID10  |                   |
| Network management     | Protocol                                | IPv6, HTTPS, UPnP, SNMP, NTP, SADP, SMTP, NFS, iSCSI, PPPoE, DDNS  |                   |
|                        | Network interface                       | 4, RJ45 10M/100M/1000M self-adaptive Ethernet interface  |                   |
| External interface     | Two-way audio input                     | 1-ch, RCA (2.0 Vp-p, 1 KΩ)   |                   |
|                        | Serial port                             | RS-232; RS-485; Keyboard   |                   |
|                        | USB interface                           | Front Panel: 1 × USB 2.0; Rear Panel: 2 × USB 3.0  |                   |
|                        | Alarm input/output                      | 16/8   |                   |
|                        | Extension board (optional)              | One extension board is supported with four 10M/100M/1000M optical interfaces (1.25 Gbps SFP module), eight RS-485 interfaces, and alarm interface of 32 alarm inputs and 16 alarm outputs.   |                   |
| General                | Power supply                            | 100 to 240 VAC, 50 to 60Hz, 5 A  |                   |
|                        | Fan                                     | Redundant dual ball bearing fan; Speed adjustable  |                   |
|                        | Consumption (without HDD)               | ≤ 140W   |                   |
|                        | Working temperature                     | 0 °C to + 50 °C (32 °F to 122 °F)  |                   |
|                        | Working humidity                        | 10% to 90%   |                   |
|                        | Dimension (W × D × H)                   | 447 × 528 × 172mm (17.6 × 20.8 × 6.8 inch)   |                   |
|                        | Weight (without HDD)                    | ≤ 23 kg (50.7 lb)  |                   |

## Physical Interfaces




| No. | Name                          | No. | Name               |
|-----|-------------------------------|-----|--------------------|
| 1   | HDMI 1/2 Video Output         | 8   | Reset Button       |
| 2   | Audio Input                   | 10  | Alarm Input        |
|     | Audio Output                  |     | Alarm Output       |
| 3   | USB 3.0                       |     | RS-485 Interface   |
| 4   | LAN                           |     | Keyboard Interface |
| 5   | eSATA Interface               | 11  | Ground             |
| 6   | VGA Video Output              | 12  | Power Supplies     |
| 7   | Mini SAS Interface (Optional) |     |                    |

## Available Models

DS-96128NI-I24; DS-96256NI-I24

Distributed by



### Headquarters

No.555 Qianmo Road, Binjiang District,  
Hangzhou 310051, China  
T +86-571-8807-5998  
overseasbusiness@hikvision.com

**Hikvision USA**  
T +1-909-895-0400  
sales.usa@hikvision.com

**Hikvision Europe**  
T +31-23-5542770  
saleseuro@hikvision.com

**Hikvision Middle East**  
T +971-4-8816086  
salesme@hikvision.com

**Hikvision Russia**  
T +7-495-669-67-99  
saleru@hikvision.com

**Hikvision India**  
T +91-22-28469900  
sales@pramahikvision.com

**Hikvision Italy**  
T +39-0438-6902  
info.it@hikvision.com

**Hikvision France**  
T +33(0)1-85-330-444  
info.fr@hikvision.com

**Hikvision Spain**  
T +34-91-737-16-55  
info.es@hikvision.com

**Hikvision Poland**  
T +48-22-460-01-50  
poland@hikvision.com

**Hikvision UK**  
T +44-1628-9021-4  
support.uk@hikvision.com

**Hikvision Singapore**  
T +65-6684-4718  
sg@hikvision.com

**Hikvision Oceania**  
T +61-2-8599-4233  
salesau@hikvision.com

**Hikvision Hong Kong**  
T +852-2151-1761

**Hikvision Canada**  
T +1-909-895-0400  
sales.usa@hikvision.com