

DS-2CD2T25FD-I5GLE/R(4mm)(Europe BV) 2 MP IR 4G Bullet Network Camera



Key Features

- Up to 2 megapixel (1920 × 1080) resolution
- Standard video compression with high compression ratio
- Progressive scan CMOS, capture motion video without incised margin
- Support dual stream, and the sub-stream for mobile surveillance
- EXIR technology, up to 50 meters IR range
- IR cut filter with auto switch
- Support 3G/4G
- 3D DNR
- Ingress Protection level: IP67



Specifications

Camera	
Image Sensor	1/2.7"CMOS Progressive Scan CMOS
Min. Illumination	0.01Lux @(F1.2,AGC ON) ,0 Lux with IR; 0.028 Lux @(F2.0,AGC ON), 0 Lux with IR
Shutter Speed	1/3 s to 1/100,000 s
Day & Night	ICR Cut Filter
Digital Noise Reduction	3D DNR
WDR	DWDR
Lens	4mm, Horizontal field of view: 86°
Lens Mount	M12
Compression Standard	
Video Compression	H.265 / H.264 / MJPEG
H.265 Type	Main Profile
Video Bit Rate	32 Kbps to 8 Mbps
Image	
Max. Resolution	1920 × 1080
Frame Rate	50Hz: 25fps (1920 × 1080,1280 × 960,1280 × 720)
Image Setting	Rotate mode, Saturation, Brightness, Contrast, Sharpness, AGC, White balance adjustable by client software or web browser
Backlight compensation	Yes, zone optional
ROI	Yes
Network	
Network Storage	Support Micro SD/Micro SDHC/Micro SDXC card (128G), local storage and NAS (NFS,SMB/CIFS)
Alarm Trigger	Motion detection, Illegal login, Tampering alarm, Network disconnect, IP address conflict, Storage full, Storage error
Protocols	TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP,NTP,UPnP,SMTP,SNMP,IGMP ,QoS,IPv6,UDP,Bonjour
General Function	One-key reset, heartbeat, mirror, password protection, privacy mask, watermark, IP address filtering
API	ONVIF(PROFILE S,PROFILE G), ISAPI,Ehome,GB28181
Interface	
Communication Interface	1 RJ45 10M/100M self-adaptive Ethernet port
4G/3G Specification	
Wireless Standards	2G: GSM 3G: WCDMA 4G: LTE-TDD、LTE-FDD
Frequency Range	GSM: 900/1800MHz WCDMA: B1/B5/B8 LTE-FDD: B1/B3/B5/B7/B8/B20 LTE-TDD: B38/B40/B41
General	
Operating Conditions	-30 °C to +60 °C (-22 °F to +140 °F), humidity 95% or less (non-condensing)
Power Supply	12 VDC ± 25%

Power Consumption and Current	Max. 8W
Protection Level	IP67
IR	50m
Dimensions	194.1×93.9×93
Weight	750g