

DS-D4219FI-CGFF **Indoor Fixed LED Display Unit**




- A variety of size design, supporting splicing, to meet the needs of various flexible sizes.
- No module shell design, die-casting aluminum case, ultra-thin thickness, beautiful and elegant.
- Lamp board front maintenance magnetic design, easy to maintain and install.
- Supports arc solution. Horizontal 0° to 90° outside the arc and vertical 10° outside the arc with more creative forms.
- Supports signal cable backup.
- Supports module rotation and horizontal and vertical mixed splicing.
- TUV-CE/ROHS/CB certificate completed.

▪ Specification

Model		DS-D4219FI-CGFF
Cabinet	Pixel Configuration	SMD Triad LED
	Pixel Pitch Category	P1.9
	Pixel Pitch	1.9531 mm (0.117")
	Modules Component	2 × 4
	Dimensions (W × H × D)	1000 mm × 500 mm × 50 mm (39.37" × 19.685" × 1.969")
	Resolution	512 × 256
	Area	0.5 m ²
	Weight	10.54 kg (23.237 lb)
	Pixel Density	262144 dots/m ²
	Lamp Board Housing	With housing
	Cabinet Material	Aluminum die casting
	Maintenance Method	Front maintenance for all components
	Cabinet Flatness	0.1 mm (0.0039")
	Protection Level	Front protection level IP60
Display	White Balance Brightness	800 cd/m ² (Peak 1000 cd/m ²)
	Color Temperature	3000 K to 10000 K adjustable
	Viewing Angle	Horizontal 160°, vertical 160°
	Contrast Ratio	≥ 5000:1
	Color Uniformity	≤ ± 0.003 Cx, Cy
	Brightness Uniformity	≥ 97%
Processing Performance	Driving Method	Constant current driving
	Frame Frequency	60 Hz
	Refresh Rate	Up to 3840 Hz
	Grey Level	Up to 18 bit
	Display Color	281 trillion
Power	Power Supply	110 to 220 VAC ± 15%
	Max. Consumption	≤ 600 W/m ²
	Average Consumption	185 W/m ²
Working Environment	Working Temperature	-10 to 40 °C (14 °F to 104 °F)
	Working Humidity	10% to 80% RH
	Storage Humidity	10% to 80% RH
	Storage Temperature	-20 to 60 °C (-4 °F to 140 °F)
General	Gross Weight	123.6 kg (272.491 lb)
	Package Dimension (W × H × D)	1333 mm × 890 mm × 744 mm (52.48" × 35.039" × 29.291") (Wooden Box, 6 cabinets in 1 box)
	Lifespan	Lamp 100,000 hours


▪ Typical Application




▪ Available Model

DS-D4219FI-CGFF

▪ Dimension





Unit: mm

▪ Accessory

▪ Included

DS-D42C04-N	DS-D42C06-N
	

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
www.hikvision.com

Follow us on social media to get the latest product and solution information.



Hikvision



HikvisionHQ



HikvisionHQ



Hikvision_Global



Hikvision
Corporate Channel



hikvisionhq

