

DS-D4229FI-CGFB **Indoor Fixed LED Display Unit**




- A variety of size design, supporting splicing, to meet the needs of various flexible sizes.
- No module shell design, die-casting aluminum case, ultra-thin thickness, beautiful and elegant.
- Lamp board front maintenance magnetic design, easy to maintain and install.
- Supports arc solution. Horizontal 0° to 90° outside the arc and vertical 10° outside the arc with more creative forms.
- Supports signal cable backup.
- Supports module rotation and horizontal and vertical mixed splicing.
- TUV-CE/ROHS/CB certificate completed.

▪ Specification

Model		DS-D4229FI-CGFB
Cabinet	Pixel Configuration	SMD Triad LED
	Pixel Pitch Category	P2.9
	Pixel Pitch	2.976 mm
	Modules Component	1 × 3
	Dimensions (W × H × D)	750 mm × 250 mm × 50 mm (29.528" × 9.843" × 1.969")
	Resolution	252 × 84
	Area	0.1875 m ²
	Weight	4.59 kg (10.12 lb)
	Pixel Density	112896 dots/m ²
	Lamp Board Housing	With housing
	Cabinet Material	Aluminum die casting
	Maintenance Method	Front maintenance for all components
	Cabinet Flatness	0.1 mm (0.00039")
	Protection Level	Front protection level IP60
Display	White Balance Brightness	800 cd/m ² (Peak 1000 cd/m ²)
	Color Temperature	3000 K to 10000 K adjustable
	Viewing Angle	Horizontal 160°, vertical 160°
	Contrast Ratio	≥ 5000:1
	Color Uniformity	≤ ± 0.003 Cx, Cy
	Brightness Uniformity	≥ 97%
Processing Performance	Driving Method	Constant current driving
	Frame Frequency	60 Hz
	Refresh Rate	Up to 3840 Hz
	Grey Level	Up to 16 bit
	Display Color	281 trillion
Power	Power Supply	110 to 220 VAC ± 15%
	Max. Consumption	≤ 600 W/m ²
	Average Consumption	< 185 W/m ²
Working Environment	Working Temperature	-10 to 40 °C (14 °F to 104 °F)
	Working Humidity	10% to 80% RH
	Storage Humidity	10% to 80% RH
	Storage Temperature	-20 to 60 °C (-4 °F to 140 °F)
General	Gross Weight	72 kg (Wooden Box, 8 cabinets in 1 box)
	Package Dimension (W × H × D)	834 mm × 427 mm × 707 mm (Wooden Box, 8 cabinets in 1 box)
	Lifespan	Lamp 100,000 hours


▪ Typical Application



▪ Available Model

DS-D4229FI-CGFB

Dimension



Unit: mm

Accessory

Optional

DS-D42C04-N LED Display Controller	DS-D42C06-N LED Display Controller
	

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
www.hikvision.com



Follow us on social media to get the latest product and solution information.

