

**DS-D47XXCF-1A/A2**  
**DS-D47XXCF-1A/A2**

- Cable package for 5 sqm screen, compatible with Aries Series and Aries Pro Series outdoor 500x1000mm :  
DS-D4729CF-1A, DS-D4729CF-1AC, DS-D4729CF-1AC/P, DS-D4739CF-1A, DS-D4739CF-1AC, DS-D4739CF-1AC/P. Default including : power supplies x1, receiving cards x1, HUB boards x1, main power cables x2, main data cables x2, power cable between cabinets x11, data cable between cabinet x11, fixation paltes x10

## ▪ Specification

Product Type	
Product Type	Spare Cables Package
Power	
Power Supply	110~220 VAC ± 15%
Working Environment	
Working Temperature	-20 °C to +45 °C (-4 °F to +113 °F )
Working Humidity	10%~90%RH (No condensation)
Storage Humidity	10%~95%RH (No condensation)
Storage Temperature	-40 °C to +60 °C (-40°F to +140 °F )
General	
Package Dimension (W × H × D)	626 (W) mm ×372 (H) mm × 402 (D) mm
Packing List	Module × 0 Main Network Cable (20 m) × 1 Main Power Cord (10 m) × 2 Cascading Network Cable × 11 Cascading Power Cord × 11 Joint Piece and Screw × 10 Driver IC × 0 Lamp Bead × 0 Power Supply × 1 Mask × 0 Power Input Aviation Plug (with Cord) × 1 Power Output Aviation Plug (with Cord) × 1 Aviation Plug for Network Interface × 1 Internal Network Cable × 1 Receiving Card × 1 Hub Board × 1
Gross Weight	14 kg/1 in 1 (30.86 lb.)

## ▪ Available Model

DS-D47XXCF-1A/A2

## ▪ Accessory



DS-D4739CF-1AC



DS-D4729CF-1A



DS-D4729CF-1AC



DS-D4739CF-1A

# See Far, Go Further



[www.hikvision.com](http://www.hikvision.com)  
[support@hikvision.com](mailto:support@hikvision.com)

