

HIKVISION®

Smart EV Charger

Charge with ease, drive at peace



1 hour charging ≈
49 km range



Full charge for 60 kWh
battery ≈ 8.5 hours



DS-TMP102-A1
(7kW)(EU)



Smarter, energy-efficient
home charging



Flexible and convenient
management



Safe and stable
protection



www.hikvision.com
support@hikvision.com



Supports **European-standard**
new-energy vehicles



Equipped with IEC62196-Type 2
connector

Product Highlights



Easy Operation

Plug-and-play, RFID, and App-based charging



Secure Design

Metal housing, emergency stop, built-in RCD



User-friendly Interface

Multiple LED indicator lights and 4.3-inch LCD for info display



Comprehensive Protection


Surge, over-current, leakage, and lightning protection

HikCharging APP Management




Charging Management

Available



Scheduled Charging

Start Time 15:16
End Time 17:16



Charging Information

0.000kWh
Charging Electricity
0h0min
Charging Duration

Product

Specifications

Input voltage: 230 VAC $\pm$ 20%, 120 VAC $\pm$ 20%

Input cable: L+N+PE

Rated output power: 7kW

Standby power consumption: 4W

Output chargers: 1

Charging cable length: 5 m

Communication: Wi-Fi, Bluetooth

DS-TMP102-A1 (7kW)(EU)

Charging interface: IEC62196-Type2

Operating temperature: -30 °C to 55 °C (-22 °F to 131 °F)

Charging mode: Mode 3

Charging connection mode: Case C

Protection rating: IP55, IK10

Installation: Wall-mount or floor-standing

Modular design: Control unit, cable unit, metering unit, status indicator, display, card reader, protection modules, etc.

Accessories

Floor Standing Pole
DS-TMP00A-A22W(EU)